



PreLak

GENERAL DESCRIPTION

Fast drying, water-based primer for use on untreated or machine sanded wooden floors in commercial, residential or sports areas.

By use of a primer the risk of side-bonding between the individual floor boards is minimised.

Protective coats with one of Junckers water based floor lacquers have to be applied after priming.

Junckers PreLak has received the Danish Indoor Climate Labelling. A product with this labelling has undergone extensive degassing and odour tests. This ensures that there are no chemical substances in the lacquer which adversely affect the air quality in the room.

For professional and private use.

PRODUCT DESCRIPTION

Product:

Water-based acrylic primer

Package sizes:

2.5 litres, 5 litres and 10 litres in Clear and white

Appearance:

Clear: Creamy/milky. Dries up to a colourless film.

White: Creamy/milky. Dries up to a transparent white film.

TECHNICAL DATA

Coverage: 8 m² per litre.

Before application: Shake/stir well before use.

Application tools:

Short hair roller. Do not apply by spraying. Don't apply by pouring out the lacquer directly on the floor.

Substrate temperature: Minimum 15° C and maximum 25° C.

Dilution: Delivered ready for use. Dilution is not recommended.

Drying time at 20° C and 50 % RH :

Approx. 1-2 hours.

RH:

Water-based products have a certain gluing effect and are therefore only recommended to be used in rooms with a stable humidity. The difference between highest and lowest RH must not fluctuate more than 30 % during the year.

Cleaning of tools: Soap and water immediately after use

Storage: Lasts for 1 year if unopened and stored at 20° C. Not to be exposed to temperatures below 5° C.

SYSTEM RECOMMENDATIONS

Junckers PreLak Clear: 1 coat, 8 m²/litre or

Junckers PreLak, White: 2 or more coats, 8 m²/liter.

+ 2 coats of a top-lacquer. Choose according to expected wear of the floor.

High traffic areas:

Finish with 2 coats of Junckers Strong, Strong Premium or HP Commercial 10 m²/litre.

Low traffic areas:

Finish with 2 coats of Junckers ProFinsh 10 m²/litre.

Sport areas:

Finish with 2 coats of Junckers HP Sport 10-12 m²/litre

Manufacturer:

Junckers Industrier A/S
www.junckers.com

Denmark:+45 70 80 30 00 / teknik@junckers.dk
ExportDept.:+45 70 80 30 00/ export@junckers.dk

Junckers Ltd. +44 1376 534700 / tech@junckers.co.uk
Junckers Hardwood (USA) +1 800 878-9663 / info@junckershardwood.com
Junckers France S.A. +33 5 5944 8518 / commercial@junckers-france.fr
Junckers Iberica S.A. +34 915 075 719 / info@junckers.es
Junckers S.r.l. +39 348 4405255 / info@junckers.it
Junckers Parkett GmbH. +49 0351-84387077 / info@junckers.de

F 5.3
2019-01-17
Replacement of
2018-06-14

DIRECTION FOR USE

Untreated/sanded floors:

The surface should be clean, dry and free from dust, wax, grease, polish etc.. Machine sand the surface to remove dirt and irregularities. Vacuum thoroughly and wipe off with a cloth well wrung in clean water.

The final sanding, before applying Junckers PreLak Clear or White should be carried out by using sandpaper grit 120-150.

PreLak, Clear:

Apply 1 coat of PreLak Clear in an even layer and leave to dry according to recommendation.

PreLak, White:

Apply 2 or more coats of PreLak White in an even layer. Make sure that overlapping edges on the lacquered area do not dry out during treatment. Between each coat, leave to dry according to recommendation. Do not apply more than 2 coats per day. Each additional coat of Junckers PreLak White will add more colour to the floor.

When the primer is dry, sand with sandpaper grit 150-180 or a black screening pad. Then finish with 2 coats of one of Junckers recommended floor lacquers.

Previously sealed floors:

Machine sand before applying Junckers PreLak. Use sandpaper grit 24-36 to strip previous coats. Then remove abrasion marks with sandpaper grit 60-80.

Finally, use sandpaper grit 120-150 to obtain a completely smooth surface.

Vacuum sanding dust and wipe off with a cloth well wrung in clean water. Prime the floor as described under "Untreated/ sanded floors".

PRECAUTIONARY MEASURES

Before using the product, read the label on the container carefully and observe the recommended precautionary measures.

See Material Safety Data Sheet for detailed information.

FURTHER INFORMATION

Products:

F 4.2 - Junckers ProFinish

F 5.1 - Junckers Strong

F 5.9 - Junckers Strong Premium

F 8.2 - Junckers HP Sport

F 8.5 - Junckers HP Commercial